

Series N600 | Dual Hose

• Hydraulics • Spray Painting • Air/Water

To handle dual 1/4" through 1/2" I.D. hose.

- Narrow frame and compact mounting base.
- Non-sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlets: 90° balanced pressure swivel joints, 1/2" female NPT threads.
- Standard outlets: 1/2" female NPT threads.
- Standard pressures to 3000 psi (207 bar), available up to 10,000 psi (690 bar) – must specify.
- Temperatures from -60°F to +250°F (-51°C to +121°C), optional temperatures to +400°F (+204°C) – must specify.
- 4-way roller assembly.
- SR and VR roller positions: swivel joint is standard on the right. TR roller positions: swivel joint is standard on the left. Other configurations available, must specify.
- Constant tension is available – consult factory.
- Reels for use with oxygen/acetylene. See Series N400 on page 8.
- Optional full flow swivel joint is available upon request. Add 1-3/4" to "F" dimension.



Standard configuration shown

PARTS DRAWING – ISO 80

Model Number	Hose Capacity of Reel feet m				Approx. Weight lb. kg			Standard Roller Assy.	Real Dimensions*** in. mm							
	I.D. in. mm	1/4 in. 6 mm	3/8 in. 10 mm	1/2 in. 13 mm	NET	UPS/FedEx SHIP Wt.	Freight SHIP Wt.		A	B	C	E	F	G	H	X
N615-19-20-10.5C		2/35	2/35	2/20	63	74*	98	N203	9	3	10.5	20.75	11.75	20	10.62	7
		2/11	2/11	2/6	29	34	44		229	76	267	527	298	508	270	178
N617-19-20-10.5I		2/50	2/50	2/25	68	84*	101	N205	11	5	10.5	20.75	13.75	20	10.62	9
		2/15	2/15	2/8	30	38	46		279	127	267	527	349	508	270	229
N615-23-24-10.5B		2/65	2/60	2/30	87	104*	122	N203	9	3	10.5	23.75	11.75	24	12.62	7
		2/20	2/18	2/9	40	47	55		229	76	267	603	298	610	321	178
N617-25-26-15.5B		2/75	2/75	2/50	93	–	128	N205	11	5	15.5	25.25	13.75	26	13.62	9
		2/23	2/23	2/15	42	–	58		279	127	394	641	349	660	346	229
N617-25-26-15.5A		2/100	2/85	–	120	–	155	N205	11	5	15.5	25.25	14.5	26	13.62	9
		2/31	2/26	–	54	–	70		279	127	394	641	368	660	346	229

Notes:

A hose stop is necessary to keep spring from unwinding.

- Specifications subject to change.
- Real models and capacities shown are for standard drag applications; for vertical lift applications, consult factory.
- Other sizes, from standard components, available on request.
- Finish: Refer to page 3.

5. Be sure to check dimensions and weights prior to ordering.

NOTICE: A flexible connector must be used between the inlet pipe and the inlet swivel joint.

*Dimensional weight may apply when shipped as a parcel package (via FedEx or UPS Ground).

*** X, Y indicate mounting holes. See page 5.

For hydraulic tool circuit applications, full flow swivels with Viton® seals are recommended (add 1.75 to "F" dimension in chart).

Available Roller Positions



SR (STD)



VR (OPT)



TR (OPT)



TR (Wallmount)

