

Series N700

- Lubrication • Air/Water • Assembly Operations
- Washdown • Air Tools • General Industrial Applications

To handle 1/4" through 1/2" I.D. hose.

- Narrow frame and compact mounting base.
- Non-sparking ratchet assembly.
- Decutching arbor to prevent damage from reverse winding.
- Standard inlet: 90° balanced pressure swivel joint, 1/2" female NPT threads.
- Standard outlet: 1/2" female NPT threads.
- Standard pressures to 3000 psi (207 bar), available up to 10,000 psi (690 bar) – must specify.
- Temperatures from -60°F to +250°F (-51°C to +121°C), optional temperatures to +400°F (+204°C) – must specify.
- 4-way roller assembly.
- SR and VR roller positions: swivel joint is standard on the right. TR roller positions: swivel joint is standard on the left. Other configurations available, must specify.
- Constant tension is available – consult factory.



Standard configuration shown



Optional Swivel Mounting Bracket

Part No. 9908-9990. For N-Series spring retractable reels, available as a kit. Conditions apply, consult factory.

PARTS DRAWING – ISO 79

Model Number	Hose Capacity of Reel feet m				Approx. Weight lb. kg			Standard Roller Assy.	Reel Dimensions*** in. mm							
	I.D. in. mm	1/4 5	3/8 10	1/2 13	NET	UPS/FedEx SHIP Wt.	Freight SHIP Wt.		A	B	C	E	F	G	H	X
N716-14-16-8C	–	25	25	52	52	64*	87	N204	10	4	8	17.62	11.25	16.25	9.12	8
	–	8	8	24	24	29	39		254	102	203	448	286	413	232	203
N716-16-17-10.5C	–	35	35	55	55	67*	90	N204	10	4	10.5	18.5	11.25	17	9.12	8
	–	11	11	25	25	30	41		254	102	267	470	286	432	232	203
†N716-17-18-8L	–	50†	50†	55	55	67*	90	N204	10	4	8	19.5	11.25	17.5	9.12	8
	–	15†	15†	25	25	30	41		254	102	203	485	286	445	232	203
N716-19-20-10.5J	–	50	50	64	64	82*	99	N204	10	4	10.5	20.75	11.25	20	10.62	8
	–	15	15	29	29	37	45		254	102	267	527	286	508	270	203
N716-23-24-15.5J	–	65	65	79	79	92*	114	N204	10	4	15.5	23.75	11.25	24	12.62	8
	–	20	20	36	36	42	52		254	102	394	603	286	610	321	203
N716-23-24-15.5G	100	75	65	94	94	101*	120	N204	10	4	15.5	23.75	11.25	24	12.62	8
	30	23	20	43	43	46	59		254	102	394	603	286	610	321	203
N716-25-26-15.5B	–	75	75	90	–	–	125	N204	10	4	15.5	25.25	11.25	26	13.62	8
	–	23	23	41	–	–	57		254	102	394	641	286	660	346	203
N718-25-26-15.5G	–	100	100	96	–	–	131	N206	12	6	15.5	25.25	13.25	26	13.62	10
	–	30	30	44	–	–	59		305	152	394	641	337	660	346	254

Notes:

A hose stop is necessary to keep spring from unwinding.

- Specifications subject to change.
- Reel models and capacities shown are for standard drag applications; for vertical lift applications, consult factory.
- Other sizes, from standard components, available on request.
- Finish: Refer to page 3.

5. Be sure to check dimensions and weights prior to ordering.

NOTICE: A flexible connector must be used between the inlet pipe and the inlet swivel joint.

*Dimensional weight may apply when shipped as a parcel package (via FedEx or UPS Ground).

***X, Y indicate mounting holes. See page 5.
†Capacity based on low pressure air hose only. Not for vertical lift applications.

Available Roller Positions



SR (STD)



VR (OPT)



TR (OPT)



TR (Wallmount)

