

PARTS DRAWING – ISO 197

Model Number For Power Rewind see Note 2	Hose Capacity of Reel feet m					Approx. Weight lb. kg		Reel Dimensions*** in. mm									
	I.D. in. mm	1-1/2 38	2 51	2-1/2 64	3 76	NET	SHIP	A	B	C	E	F POWER	F POWER with I-Stub	G	H	X	Y
	O.D. in. mm	2.06 52	2.67 68	3.25 83	3.78 96												
V-5111-48-50-20	50 15	- -	- -	- -	- -	310 141	385 175	10.63 270	2.5 64	20 508	48 1219	17.5 445	- -	50 1270	26 660	8.63 219	28 711
V-5111-56-58-20	75 23	- -	- -	- -	- -	330 150	405 184	10.63 270	2.5 64	20 508	56 1422	17.5 445	- -	58 1473	30 762	8.63 219	28 711
V-5111-62-64-20	100 30	- -	- -	- -	- -	340 154	415 188	10.63 270	2.5 64	20 508	62 1575	17.5 445	- -	64 1626	33 838	8.63 219	28 711
V-5218-56-58-24	- -	50 15	- -	- -	- -	370 168	445 202	11.5 292	3.63 92	20 508	56 1422	19.25 489	- -	58 1473	30 762	9.5 241	28 711
V-5218-62-64-24	- -	75 23	- -	- -	- -	390 177	465 211	11.5 292	3.63 92	20 508	62 1575	19.25 489	- -	64 1626	33 838	9.5 241	28 711
V-5218-70-72-24	- -	100 30	- -	- -	- -	400 181	475 215	11.5 292	3.63 92	20 508	70 1778	19.25 489	- -	72 1829	37 940	9.5 241	28 711
V-5319-62-64-30	- -	- -	50 15	50 15	- -	400 182	475 216	12.25 311	4.38 111	30 762	62 1575	21.25 540	20.5 521	64 1626	33 838	10.25 260	28 711
V-5319-70-72-30	- -	- -	75 23	- -	- -	410 186	485 220	12.25 311	4.38 111	30 762	70 1778	21.25 540	20.5 521	72 1829	37 940	10.25 260	28 711
V-5319-78-80-30	- -	- -	100 30	- -	- -	420 191	495 225	12.25 311	4.38 111	30 762	78 1981	21.25 540	20.5 521	80 2032	41 1041	10.25 260	28 711

Notes:

- Specifications subject to change.
 - When ordering power rewind models, prefix model number with:
 - V-A** = Air Rewind reels are supplied with control valve and 25" air hose.
 - V-EP** = Electric Rewind (2/3 HP) 12v and 24v DC rewind reels are supplied with switch and solenoid.
 - V-HD** = Hydraulic Rewind reels are not supplied with control valve.
 - Be sure to check dimensions and weights prior to ordering.
- NOTICE:** A flexible connector must be used between the inlet pipe and the inlet swivel joint.
- ***X, Y indicate mounting holes. See page 2.

