

Series V-N800

To handle 1" I.D. hose.

- Narrow frame and compact mounting base.
- Non-sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- #304 stainless steel internals.
- Standard inlet: 90° #304 stainless steel ball bearing swivel joint, 1" female NPT threads.
- Standard outlet: 1" female NPT threads.
- Standard pressures to 1000 psi (69 bar).
- Temperatures from -40°F to +250°F (-40°C to +121°C).
- 4-way roller assembly.



Optional TR roller position shown

PARTS DRAWING – ISO 81

Model Number	Hose Capacity of Reel		Approx. Weight		Standard Roller Assy.	Reel Dimensions***							
	feet m		lb. kg			in. mm							
	I.D. in. mm	± 25	NET	Freight SHIP WT.		A	B	C	E	F	G	H	X
V-N816-25-26-10.5B	35	96	131	N204	10	4	10.5	25.25	14.25	26	13.62	8	
	11	44	59	N204	254	102	267	641	362	660	346	203	
V-N818-25-26-10.5B	50	102	137	N206	12	6	10.5	25.25	16.25	26	13.62	10	
	15	46	62	N206	305	152	267	641	413	660	346	254	

Notes:

A hose stop is necessary to keep spring from unwinding.

1. Specifications subject to change.
2. Reel models and capacities shown are for standard drag applications; for vertical lift applications, consult factory.
3. Other sizes, from standard components, available on request.
4. **Finish:** Refer to page 2.
5. **Be sure to check dimensions and weights prior to ordering.**

NOTICE: A flexible connector must be used between the inlet pipe and the inlet swivel joint.

*** X, Y indicate mounting holes. See page 2.

Available Roller Positions